

JAN. 2007

**ZIEMAN MODEL 1160 TRAILER
TAGALONG - DECK BETWEEN FENDERS
SMALL SKID-STEER SPECIAL**

G.V.W.R.: 9,999 lbs. at 55+ M.P.H.

PAYLOAD CAPACITY: 8,000 lbs. at 55+ M.P.H.

TRAILER WEIGHT: 2,000 lbs.

HITCH WEIGHT: 800 lbs. required at MAXIMUM payload capacity. Any reduction of the payload below the maximum will reduce the required hitch weight accordingly.

OVERALL LENGTH: 16 feet, 0 inches w/ electric brakes. 16 feet, 5 inches w/ surge brakes. Overall length includes ramp overhang.

OVERALL WIDTH: 100 inches.

TONGUE LENGTH: 5 feet, 5 1/2 inches.

DECK LENGTH: 10feet.

DECK WIDTH: 71 3/4 inches, inside rails.

WIDTH BET. FENDERS: 81 1/4 inches.

DECK HEIGHT: 17 1/2 inches. (loaded)

HITCH HEIGHT: 14" to 23" adj. in 3" increment (elect. brk.)
21 1/2" to 25 1/2" (surge brk.)

RAMP LOAD ANGLE: 14 degrees.

DECKING: 2" x 12" Douglas Fir, laid lengthwise.

HITCH: 2-5/16" ball coupler or 2.5" I.D. Lunette eye. Attached to a drilled plate with four 5/8" diameter grade 8 bolts and grade C locknuts.

AXLES: Two 6,000 lb. rated each.

BRAKES: Standard: 12"x 2" electric drum brakes. Optional: surge hydraulic disc brake. Brake systems include emergency breakaway protection.

TIRES: Four ST225/75R15 (D) 8 P.R. Tubeless, radials.

ZIEMAN MODEL 1160 CONT.

- WHEELS:** Four 15 x 6.00 DC, steel disc with 6 lugs on a 5-1/2" diameter bolt circle.
- SUSPENSION:** Heavy duty torsion axle with fully independent suspension
- TIE DOWN RINGS:** Two D-Rings per side. 5/8" diameter stock.
- TONGUE JACK:** Screw type, swing-away with sand pad (5000 lb).
Optional: H.D. 12,000 lb., quick drop, center mounted jack.
- ELECTRICAL PLUG:** A.T.A. standard 7-way RV.
- LIGHTING:** 12 volt, to D.O.T. standards.
- SAFETY CHAIN:** Two 5/16" High Test chain (Grade 70)
- RAMPS:** Steel, 60" x 18" wide. Surfaces are inverted angles. Adjustment is from 68" outside to 21" inside. Ramps are in vertical position when transporting.(Spring assisted)
- STRUCTURAL:** Constructed of A-36 Grade steel and engineered to exceed the rated capacity.
- Deck main rails: 6" channels
Deck side rails: 6" channels
Cross members: 3" channels
- The deck side rails are the main rails.
-
- The tongue is a continuation of the main rails, so there are two one-piece channels from the hitch through the rear cross member, cold formed.