

JAN. 2007

ZIEMAN MODEL 1170 - TILT TYPE TRAILER
TAGALONG - DECK BETWEEN FENDERS

G.V.W.R.: ** 15,000lbs. at 55 M.P.H. w/ electric brakes.

PAYLOAD CAPACITY: ** 12,000lbs. at 55 M.P.H.

TRAILER WEIGHT: 3,000lbs.

HITCH WEIGHT: ** 2,832lbs. required at MAXIMUM Payload capacity. Any reduction of the payload below the maximum will reduce the required hitch weight accordingly.

OVERALL LENGTH: 27 feet, 0 inches.

OVERALL WIDTH: 102 inches.

TONGUE LENGTH: 5 feet, 11 inches.

DECK LENGTH: 16 feet tilt + 4 feet stationary.

DECK WIDTH: 78 1/4 inches.

WIDTH BET. FENDERS: 82 inches (81 1/2" between tires).

DECK HEIGHT: 22 inches. (loaded)

HITCH HEIGHT: 17.5" to 26.5" adj. in 3" increments.
22.5" to 28.5" (surge brk.)

LOAD ANGLE: 12 degrees.

DECKING: Wood, Douglas fir, laid lengthwise.

HITCH: 2-5/16" Ball or 2.5" I.D. Lunette eye. Attached to a drilled plate with four 5/8" diameter grade 8 bolts and grade C locknuts.

AXLES: Two Torsion axles. 6,100 lb. each.

BRAKES: Standard: 12" x 2" electric drum brakes

All brake systems include emergency breakaway protection.

TIRES: Four 235/80R16 (E) 10 Ply rating. Tubeless, radials.

ZIEMAN MODEL 1170 CONT.

WHEELS: Four 16 x 6 DC, steel disc with 8 lugs on a 6-1/2" diameter bolt circle.

SUSPENSION: Heavy duty torsion axle with fully independent suspension.

TIE DOWN RINGS: FIVE D-rings per side, 5/8" diameter stock.

ELECTRICAL PLUG: A.T.A. standard 7-way.

LIGHTING: 12 volt, to D.O.T. standards.

TONGUE JACK: Retractable, crank type with 12,000 lb. static rating. With 12" quick-retract leg.

SAFETY CHAIN: Two 5/16" High Test chain (Grade 70)

STRUCTURAL: Constructed of A-36 Structural Grade steel and engineered to exceed the rated capacity.

Deck main rails: 7" x 9.8 lb. channels
Perimeter rail: 3" x 5" x 3/8" angle
Cross members: 3" x 3.5 lb. channels
Tongue rails: 7" x 9.8 lb. channels