

**ZIEMAN MODEL 1256 - TILT w/FLIP DOWN RAMPS TRAILER
TAGALONG - DECK BETWEEN FENDERS**

G.V.W.R.: ** 14,600 lbs. at 55+ M.P.H.

PAYLOAD CAPACITY: ** 11,500 lbs. at 55+ M.P.H.

TRAILER WEIGHT: 3,100 lbs.

HITCH WEIGHT: ** 2,832 lbs. required at MAXIMUM payload capacity. Any reduction of the payload below the maximum will reduce the required hitch weight accordingly.
** 2,000 lbs max hitch weight with surge brakes.

OVERALL LENGTH: 18 feet 9 inches.
19 feet 2 inches w/ surge brakes

OVERALL WIDTH: 89 inches.

TONGUE LENGTH: 5 feet, 11 inches.

DECK LENGTH: 12 feet.

DECK WIDTH: 60 inches.

WIDTH BET. FENDERS: 72 inches.

DECK HEIGHT: 15 inches. (loaded)

HITCH HEIGHT: 15" to 24" adj. in 3" increments.
15.25" to 21.25" (surge brk.)

DECKING: Steel, 1/4" diamond plate.

TILT & RAMP ANGLE: 8.6 degrees. (with bed tilted)

RAMPS: Steel, 42" long x 20 3/4" wide. Ramp spacing is adjustable from 60" outside to 24" inside. The ramp surfaces are diamond plate. Stabilizer legs are an integral part of the ramps. Ramps are vertical for transport.

TILT CYLINDER: One 2 1/2" x 10" with internal oil transfer.

HITCH: 2-5/16" ball or 2.5" I.D. lunette eye
Attached to a drilled plate with four 5/8" diameter grade 8 bolts and grade C locknuts.

AXLES: Two Dexter or Alko 7,000 lbs. rated, rubber torsion axles.

ZIEMAN MODEL 1256 CONT.

SUSPENSION: Heavy duty torsion axle with fully independent suspension.

BRAKES: Standard: 12"x 2" electric drum brakes on all wheels.
 *** Optional: 12"x 2" surge actuated hydraulic drum brakes on all wheels.
 All brake systems include emergency breakaway protection.

TILT CYLINDER: One HYPOWER LC-2510 w/#33 hole in piston.

TIRES: Four LT235/85R16 (E) 10 ply rating.
 Tubeless, radials.

WHEELS: Four 16 x 6 DC steel disc with 8 lugs on a 6-1/2" diameter bolt circle.

TIE DOWN RINGS: Two D-rings per side. (5/8" dia. material)

TONGUE JACK: Retractable, crank type with 12,000 lb. static rating. With 12" quick-retract leg.

SAFETY CHAIN: Two 5/16" high test chain (Grade 70) with safety hook.

ELECTRICAL PLUG: A.T.A. standard 6-way.

LIGHTING: 12 volt, to D.O.T. standards.

COLOR: Zieman charcoal gray.

STRUCTURAL: Constructed of A-36 structural grade steel and engineered to exceed the rated capacity.

Deck main rails: 7" x 9.8 lb. channels
 Deck side rails: 7" x 9.8 lb. channels
 Crossmembers: 3" x 4.1 lb. channels
 Tongue rails: 6" x 8.2 lb. channels

The deck side rails are the main rails.

** (Surge brakes reduce G.V.W.R, capacity and hitch weight by 832 lbs.)