

**ZIEMAN MODEL 2357-S TILT TYPE TRAILER
TAGALONG - DECK OVER WHEELS
3 AXLE, TILT + STATIONARY**

G.V.W.R.: * 62,000 lbs. at 55 + M.P.H.

PAYLOAD CAPACITY: * 50,000 lbs. at 55 + M.P.H. ** (APPROXIMATE)

TRAILER WEIGHT: 12,000 lbs.

HITCH WEIGHT: * 8,000 lbs. required at MAXIMUM payload capacity. Any reduction of the payload below the maximum will reduce the required hitch weight accordingly. 15,000 lb. max. rated.

OVERALL LENGTH: 36 feet.

OVERALL WIDTH: 102 inches.

TONGUE LENGTH: 6 feet, 10 inches.

TILT DECK LENGTH: 24 feet.

STATIONARY DECK: 5 feet.

DECK WIDTH: 102 inches.

DECK HEIGHT: 36 1/2 inches. (loaded)

HITCH HEIGHT: 22" to 31" adjustable in 2 1/4" steps.

TILT ANGLE: 11.7 to 12.0 degrees.

DECKING: Wood, 2" x 12" Purpleheart. Purpleheart is a dense and straight grain wood. It is a very durable and shrink resistant wood which make is much superior to that of oak.

HITCH: Alloy steel lunette with 3" I.D. eye. Attached to a drilled plate with four 3/4" diameter grade 8 bolts and grade C locknuts.

TILT CYLINDERS: Two 3" x 12" with internal oil transfer.

AXLES: Three 22,500 lb. rated each. 5" O.D. x .440" wall tube with oil hubs and Stemco seals.

BRAKES: 12 1/4" x 7 1/2", S-cam straight air drum brakes on all wheels. Includes emergency breakaway protection and anti-lock brake system, 4S/2M.

ZIEMAN MODEL 2357-S CONT.

TIRES: Twelve 215/75R17.5, Test Index H.
Tubeless, steel belted radials.

WHEELS: Twelve 17.5 x 7.5, steel disc with 10 lugs on
an 8-3/4" diameter bolt circle.

SUSPENSION: Hutch 9700 Tri-axle 2-leaf slipper springs (6)
with load equalizers. 67200 lb. rating.

HEADBOARD: 6 inch headboard.

BUMPER: 4 inch square tube under ride guard approx. 21
inches above the ground.

TIE DOWN RINGS 6 1" dia. section D-rings per side. (12 total)

TONGUE JACK: Retractable, two speed crank type with 25,000 lb.
static rating. With 12" quick-retract leg.

SAFETY CHAINS: Two 1/2" High Test chains (Grade 70) with
safety hooks. Crossover type.

TILT LOCK: Spring loaded tilt lock with safety pin.

DAMPER: Two 3" x 12" tilt dampening cylinders.

ELECTRICAL PLUG: A.T.A. standard 7-way, w/ ABS cable.

LIGHTING: **L.E.D.**, 12 volt, to D.O.T. standards.

PAINT: Charcoal gray polyurethane.

STRUCTURAL: Constructed of A-36 structural grade steel
and engineered to exceed the rated capacity.

Deck main rails: 10" x 19 lb. I-beams
Deck side rails: 8" x 11.5 lb. channels
Crossmembers: 2" x 5" x 3/16" wall tube
and 5" x 6.7 lb. channels
Drawframe rails: 14" x 26 lb. I-beams

The crossmembers are pierced through
the main rails for greater rigidity.

* Trailer capacity is above legal limit
in some jurisdictions.