

**ZIEMAN MODEL 2650 - BEAVERTAIL, RAMP TRAILER
TAGALONG - DECK OVER WHEELS**

G.V.W.R.: 25,990 lbs. at 55+ M.P.H.

PAYLOAD CAPACITY: 21,000 lbs. at 55+ M.P.H.

TRAILER WEIGHT: 4,440 lbs.

HITCH WEIGHT: 5,990 lbs. required at Maximum payload capacity. Any reduction of the payload below the maximum will reduce the required hitch weight accordingly.

OVERALL LENGTH: 29 feet (including ramp overhang).

OVERALL WIDTH: 100 inches.

TONGUE LENGTH: 9 feet - 0 inches.

DECK LENGTH: 20 feet - 0 inches (including beavertail).

BEAVERTAIL LENGTH: 38 inches. (center part of beavertail is opened for bucket storage).

DECK WIDTH: 100 inches. The wooden deck lays flush with the perimeter rails.

DECK HEIGHT: 36 inches. (loaded)

HITCH HEIGHT: 25" to 31 3/4" adjustable in 2 1/4" steps.

CLIMB ANGLE: Ramp = 15.7 degrees
Beavertail = 18 degrees

RAMPS: SPRING ASSISTED Steel, 64" long x 21.25" wide. Ramp spacing is adjustable from 96.5" outside to outside to 40.5" inside to inside. Ramp surfaces are inverted angles for traction. Stabilizer legs are part of ramps. Ramps are in vertical position when transporting. OPTIONAL Aluminum ramps are available.

DECKING: Wood, 2" x 12" Douglas Fir, laid lengthwise.

HITCH: Alloy steel Lunette with 3" I.D. eye. Attached to a drilled plate with four 3/4" diameter grade 8 bolts and grade C locknuts.

AXLES: Two 10,000 lb. rated each.
5" O.D. x 1/4" wall tube with oil bath hubs.

ZIEMAN MODEL 2650 CONT.

BRAKES: Standard: 12-1/4" x 3-1/2" electric drum brakes on all wheels. Brake system includes emergency breakaway protection.

TIRES: Eight ST235/80R16 (E), 10 ply rating. Tubeless, radials.

WHEELS: Eight 16 x 6 DC, steel disc with 10 lugs on a 8-3/4" diameter bolt circle.

SUSPENSION: Tandem 5-leaf slipper springs with load equalizers. 20,000 lb. rating.

TONGUE JACK: Retractable, crank type with 12,000 lb. static rating. With 12" quick-retract leg.

TIE DOWN RINGS: THREE D-rings per side. 1" diameter stock.

SAFETY CHAIN: Two 3/8" High Test chains (Grade 70) with safety hooks. Crossover type.

ELECTRICAL PLUG: A.T.A. standard 7-way.

LIGHTING: 12 volt, to D.O.T. standards.

COLOR: Zieman charcoal gray.

STRUCTURAL: Constructed of A-36 Structural Grade steel and engineered to exceed the rated capacity.

Deck Main Rails: 10" x 15 lb. I-beams
Deck Side Rails: 6" x 8.2 lb. channels
Crossmembers: 3" x 3.5 lb. channels
Tongue Rails: 10" x 15 lb. I-beams

The Tongue is a continuation of the Main Rails so there are two one-piece I-beams from the Hitch to the Beavertail.