

**ZIEMAN MODEL 2660 - BEAVERTAIL, RAMP TRAILER
TAGALONG - DECK OVER WHEELS**

G.V.W.R.: 25,000 lbs. at 55 M.P.H.

PAYLOAD CAPACITY: 19,000 lbs. at 55 M.P.H.

TRAILER WEIGHT: 6,000 lbs.

HITCH WEIGHT: 5,000 lbs. required at Maximum payload capacity. Any reduction of the payload below the maximum will reduce the required hitch weight accordingly.

OVERALL LENGTH: 33 feet, 1 inches (including ramp overhang)

OVERALL WIDTH: 102 inches.

TONGUE LENGTH: 6 feet, 7 inches.

DECK LENGTH: 25 feet. (including Beavertail)

BEAVERTAIL LENGTH: 60 inches. (center part of beavertail is opened for bucket storage).

DECK WIDTH: 102 inches. The wooden deck lays flush with the perimeter rails.

DECK HEIGHT: 36 inches. (loaded)

HITCH HEIGHT: 25" to 31 3/4" adjustable in 2 1/4" steps.

CLIMB ANGLE: Ramp = 14.4 degrees
Beavertail = 14.3 degrees

RAMPS: SPRING ASSISTED Steel, 64" long x 21.25" wide. Ramp spacing is adjustable from 96.5" outside to outside to 40.5" inside to inside. Ramp surfaces are inverted angles for traction. Stabilizer legs are part of ramps. Ramps are in vertical position when transporting. OPTIONAL Aluminum ramps are available.

DECKING: Wood, 2" x 12" Douglas Fir, laid lengthwise.

HITCH: Alloy steel Lunette with 3" I.D. eye. Attached to a drilled plate with four 3/4" diameter grade 8 bolts and grade C locknuts.

AXLES: Two Hayes 10,000 lb. rated each.
5" O.D. x 1/4" wall tube with oil bath hubs.

ZIEMAN MODEL 2660 CONT.

BRAKES: Standard: 12-1/4" x 3-1/2" electric drum brakes on all wheels.
Optional: 12-1/4" x 5" S-cam straight air drum brakes on all wheels. Anti-lock brake system, 2S/1M. (Adds 200 lb.weight)
All brake systems include emergency breakaway protection.

TIRES: Eight LT235/85R16 (E), 10 ply rating. Tubeless, radials.

WHEELS: Eight 16 x 6 DC, steel disc with 8 lugs on a 6-1/2" diameter bolt circle.

SUSPENSION: Hutch H-9700 tandem 2-leaf slipper springs with load equalizers. Rating exceeds axles.

TONGUE JACK: Retractable, crank type with 12,000 lb. static rating. With 12" quick-retract leg.

TOOL BOX: 14 Ga. steel, 10" high x 15" wide x 24" long, mounted on tongue.

TIE DOWN RINGS: Four D-rings per side. 1" diameter stock.

SAFETY CHAIN: Two 3/8" High Test chains (Grade 70) with safety hooks. Crossover type.

ELECTRICAL PLUG: A.T.A. standard 6-way for electric brakes.
A.T.A. standard 7-way for air brakes.

LIGHTING: **L.E.D.**, 12 volt, to D.O.T. standards.

COLOR: Zieman charcoal gray.

STRUCTURAL: Constructed of A-36 Structural Grade steel and engineered to exceed the rated capacity.

Deck Main Rails: 10" x 15 lb. I-beams
Deck Side Rails: 6" x 8.2 lb. channels
Crossmembers: 3" x 4.1 lb. channels
Tongue Rails: 10" x 15 lb. I-beams
The Tongue is a continuation of the Main Rails so there are two one-piece I-beams from the Hitch to the Beavertail.