

**ZIEMAN MODEL 2715HD HEAVY DUTY SPL. - BEAVERTAIL, RAMP TRAILER
TAGALONG - DECK OVER WHEELS (AIR MODEL ONLY)**

G.V.W.R.: 34,000 lbs. at 55 M.P.H.

PAYLOAD CAPACITY: 26,000 lbs. at 55 M.P.H.

TRAILER WEIGHT: 7,900 lbs.

HITCH WEIGHT: 6,000 lbs. required at Maximum payload capacity. Any reduction of the payload below the maximum will reduce the required hitch weight accordingly.

OVERALL LENGTH: 33 feet 11 inches. (including ramp overhang)

OVERALL WIDTH: 102 inches.

TONGUE LENGTH: 7 feet 2 inches.

DECK LENGTH: 25 feet. (including Beavertail)

BEAVERTAIL LENGTH: 48 inches. (center part of beavertail is opened for bucket storage).

DECK WIDTH: 102 inches. The wooden deck lays flush with the perimeter rails.

DECK HEIGHT: 34 inches (loaded).

HITCH HEIGHT: 21 1/4" to 28" adjustable in 2 1/4" steps.

CLIMB ANGLE: Ramp = 16.0 degrees
Beavertail = 12.9 degrees

RAMPS: SPRING ASSISTED Steel, 64" long x 21.25" wide. Ramp spacing is adjustable from 96 1/2" outside to outside to 40 1/2" inside to inside. Ramp surfaces are inverted angles for traction. Stabilizer legs are part of ramps. Ramps are in vertical position when transporting. OPTIONAL Aluminum ramps are available.

DECKING: Wood, 2" x 12" Purpleheart. Purpleheart is a dense and straight grain wood. It is a very durable and shrink resistant wood which make is much superior to that of oak.

HITCH: Alloy steel Lunette with 3" I.D. eye. Attached to a drilled plate with four 3/4" diameter grade 8 bolts and grade C locknuts.

ZIEMAN MODEL 2715HD HEAVY DUTY SPL. CONT.

AXLES: Two Hayes 16,000 lb. rated each.
5 1/8" O.D. x 7/16" wall tube with oil hubs.

BRAKES: Standard: 12 1/4" x 5 1/2" S-cam straight air drum brakes on all wheels. Anti-lock brake system, 2S/1M. All brake systems include emergency breakaway protection.

TIRES: Eight 215/75R17.5 (H), Tubeless, radials.

WHEELS: Eight 17.5 x 6.75 DC, steel disc with 10 lugs on a 8-3/4" diameter bolt circle.

SUSPENSION: Hutch H-9700 tandem 2-leaf slipper springs with load equalizers. Rating exceeds axles.

TONGUE JACK: Retractable, crank type with 12,000 lb. static rating. With 12" quick-retract leg.

TOOL BOX: 14 Ga. steel, 10" high x 15" wide x 24" long, mounted on tongue.

TIE DOWN RINGS: Four D-rings per side. 1" diameter stock.

SAFETY CHAIN: Two 3/8" High Test chains (Grade 70) with safety hooks. Crossover type.

ELECTRICAL PLUG: A.T.A. standard 7-way for air brakes.

LIGHTING: **L.E.D.**, 12 volt, to D.O.T. standards.

COLOR: Zieman charcoal gray.

STRUCTURAL: Constructed of A-36 Structural Grade steel and engineered to exceed the rated capacity.
Deck Main Rails: 12" x 19 lb. I-beams
Deck Side Rails: 6" x 8.2 lb. channels
Crossmembers: 5" x 6.7 lb. channels

Tongue Rails: Continuation of the Main Rails.
Crossmembers are pierced through the Main Rails.